



8900 Series Submittal Data

JOB NAME: _____

LOCATION: _____

ARCH/ENGR: _____

CONTRACTOR: _____

MODEL NO: _____

TYPE GAS: _____

BTU INPUT/OUTPUT: _____

ADDITIONAL INFORMATION:

Standard Features

- 81% Efficiency
- Bronze Headers (Water Heaters)
- Cast Iron Headers (Boilers)
- Structural Steel Frame
- Front Mount 24V Controls
- Threaded Connections
- Field Reversible Headers
- 2-Pass Finned Copper Tube Heat Exchanger
- Slide Out Heat Exchanger
- Slide Out Burner Tray
- ASME Pressure Relief Valve Mounted
- 2 ½" Interlocking Combustion Chamber
- Integral Draft Hood
- Thermometer
- Temperature/Pressure Gauge
- 115/24V Transformer
- Indoor Installation
- Flow Switch Mounted and Wired
- IID, Spark Ignition Control
- Manual Reset High Limit
- Operating Aquastat
- Pump Delay Relay 9 Amp
- Leak Test Valves
- FM/CSD-1 Gas Train Compliant
- On/Off Firing

Optional Equipment

- 2 Stage Firing
- 4 Stage Firing (Spark Ignition Only)
- Modulation (Flame Safeguard)
- Propane Gas
- Flame Safeguard Control
- Cupronickel Heat Exchanger
- Single Pass Heat Exchanger
- Wired & Mounted Flange
- 5' Pump Pigtail
- Alarm Bell
- Flame Failure Dry Contact
- Main Flame Status Relay
- Enable/Disable Relay 24V
- Enable/Disable Relay 120V
- Low Gas Pressure Switch
- High Gas Pressure Switch
- Left Hand Gas Connection
- Right Hand Water Connection
- Dual Flue (840 – 1900)
- Power Venter Wiring
- Three Phase Pump Contactor
- Single Phase Pump Contactor
- Keyboard Display Module
- Light Package
- Remote/Local Switch
- Sidewall Vent Kit
- Vent Termination Hood
- Pump

Gas Trains

- CSD-1 Code
- Kentucky Code