



Dominator Series Submittal Data

JOB NAME: _____

LOCATION: _____

ARCH/ENGR: _____

CONTRACTOR: _____

MODEL NO: _____

TYPE GAS: _____

BTU INPUT/OUTPUT: _____

ADDITIONAL INFORMATION:

Standard Features

- 85.1% Efficiency
- Bronze Headers (Water Heaters)
- Cast Iron Headers (Boilers)
- Integral PID Staging Control
- Outdoor Reset
- Low NO_x
- Slide Out Heat Exchanger
- Finned Copper Tube Heat Exchanger
- Tekmar Sensor
- Low Voltage Controls
- ASME Pressure Relief Valve Mounted
- Pump Delay Control
- LED Diagnostic Panel
- Uginox Alloy Stainless Steel Burners
- 2 Stage Firing (300 – 2100)
- 4 Stage Firing (1050 – 2100)
- Sealed Combustion Chamber
- Temperature/Pressure Gauge (Boilers)
- Flow Switch Mounted and Wired
- FM Compliant Gas Train
- Category I or III Venting
- Leak Test Valves
- Side Combustion Air Intake (300 – 2100)
- Rear Combustion Air Intake (750 – 2100)
- Direct Vent up to 35' Equivalent
- SCAQMD Rule 1146.2
- Ventura County APCD Rule 74.11.1
- CSA Designed Certified and Listed
- National Board Certified

Optional Equipment

- Propane Gas
- Cupronickel Heat Exchanger
- Wired & Mounted Flange
- 5' Pump Pigtail
- Alarm Bell
- Flame Failure Dry Contact
- Main Flame Status Contact
- Enable/Disable Relay 24V
- Enable/Disable Relay 120V
- Low Gas Pressure Switch
- High Gas Pressure Switch
- Right Hand Water Connection
- C.A.D. Dry Contact
- Freeze Protection Kit
- Stainless Steel Jacket
- Power Venting Wiring
- Three Phase Pump Contactor
- Remote/Local Switch
- Sidewall Vent Kit
- Sidewall Vent Kit w/Air Intake Hood
- Vent Termination Hood
- Air Intake Hood
- Barometric Damper
- Outdoor Installation
- Pump
- Rack Kit

Gas Trains

- CSD-1 Code
- Kentucky Code