



260 North Elm Street Westfield, MA 01020

Factory Primed Equipment:

Vulcan Radiator Commercial Finned Tube provides the Lino-Vector II, Vanguard, LC-209 and LC-210 products with a prime paint finish as standard. The prime finish can be field painted with another coat of a desired color of finish paint. The standard factory furnished prime paint finish is an epoxy-polyester powder coating material, electrostatic applied and oven cured. The finish gloss is 50 based on ASTM D523.

Applying an exterior finish coat of paint over a prime finished enclosure provided by Vulcan Radiator will not affect the product warranty.

Field Painting: Touch-up

The surface should be prepared by lightly sanding prior to application of the paint. After sanding, wipe the surface with a tack or solvent rag to remove dirt, grit, grease or body oils left during handling. For field touch-up, spray cans supplied by Vulcan can be used.

Field Painting: Full Recoat

For full recoat, lightly sand and wipe the surface with a tack or solvent rag to remove dust, grit, grease or body oils left during handling.

Apply an industrial grade solvent borne paint with a urethane or epoxy base. Do not use latex or waterborne paints. Industrial grade paints should be available at paint stores such as Sherwin Williams, Benjamin Moore, etc.

Follow any additional recommended surface preparation procedures from the finish coat supplier.

Note: It is generally recommended to coat a small non-visible area first to insure color match and coating compatibility before painting the entire job.